

SolarEdge Single Phase Inverters For North America

SE3000A-US / SE3800A-US / SE5000A-US / SE6000A-US /
SE7600A-US / SE10000A-US / SE11400A-US

Authorized Agent:



香港可再生能源有限公司
Hong Kong Renewable Energy Co. Ltd.

INVERTERS



The best choice for SolarEdge enabled systems

- Integrated arc fault protection (Type 1) for NEC 2011 690.11 compliance
- Superior efficiency (98%)
- Small, lightweight and easy to install on provided bracket
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- Outdoor and indoor installation
- Fixed voltage inverter, DC/AC conversion only
- Pre-assembled AC/DC Safety Switch for faster installation

	SE3000A-US	SE3800A-US	SE5000A-US	SE6000A-US	SE7600A-US	SE10000A- US	SE11400A-US	
OUTPUT								
Nominal AC Power Output	3300	3840	5000	6000	7680	9980 @ 208V 10000 @240V	11520	VA
Max. AC Power Output	3650	4150	5400 @ 208V 5450 @ 240V	6000	8350	10800 @ 208V 10950 @ 240V	12000	VA
AC Output Voltage Min.-Nom.-Max.* 183 - 208 - 229 Vac	-	-	✓	-	-	✓	-	
AC Output Voltage Min.-Nom.-Max.* 211 - 240 - 264 Vac	✓	✓	✓	✓	✓	✓	✓	
AC Frequency Min.-Nom.-Max.*	59.3 - 60 - 60.5 (with HI country setting 57 - 60 - 60.5)							Hz
Max. Continuous Output Current	14	16	24 @ 208V 21 @ 240V	25	32	48 @ 208V 42 @ 240V	48	A
GFDI	1							A
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes							
INPUT								
Recommended Max. DC Power** (STC)	4100	4800	6250	7500	9600	12400	14400	W
Transformer-less, Ungrounded	Yes							
Max. Input Voltage	500							Vdc
Nom. DC Input Voltage	325 @ 208V / 350 @ 240V							Vdc
Max. Input Current***	11	13	16.5 @ 208V 15.5 @ 240V	18	23.5	33 @ 208V 30.5 @ 240V	35	Adc
Max. Input Short Circuit Current	30							Adc
Reverse-Polarity Protection	Yes							
Ground-Fault Isolation Detection	600k Ω Sensitivity							
Maximum Inverter Efficiency	97.7	98.2	98.3	98.3	98	98	98	%
CEC Weighted Efficiency	97.5	98	97.5 @ 208V 98 @ 240V	97.5	97.5	97 @ 208V 97.5 @ 240V	97.5	%
Nighttime Power Consumption	< 2.5				< 4			W
ADDITIONAL FEATURES								
Supported Communication Interfaces	RS485, RS232, Ethernet, ZigBee (optional)							
STANDARD COMPLIANCE								
Safety	UL1741, UL1699B, UL1998 , CSA 22.2							
Grid Connection Standards	IEEE1547							
Emissions	FCC part15 class B							
INSTALLATION SPECIFICATIONS								
AC output conduit size / AWG range	3/4" minimum / 24-6 AWG				3/4" minimum / 8-3 AWG			
DC input conduit size / # of strings / AWG range	3/4" minimum / 1-2 strings / 24-6 AWG				3/4" minimum / 1-2 strings / 14-6 AWG			
Dimensions with AC/DC Safety Switch (HxWxD)	30.5 x 12.5 x 7 / 775 x 315 x 172		30.5 x 12.5 x 7.5 / 775 x 315 x 191		30.5 x 12.5 x 10.5 / 775 x 315 x 260			in / mm
Weight with AC/DC Safety Switch	51.2 / 23.2		54.7 / 24.7		88.4 / 40.1			lb / kg
Cooling	Natural Convection				Fans (user replaceable)			
Noise	< 25				< 50			dBA
Min.-Max. Operating Temperature Range	-13 to +140 / -25 to +60 (CAN version**** -40 to +60)							°F / °C
Protection Rating	NEMA 3R							

Authorized Agent:



香港可再生能源有限公司
Hong Kong Renewable Energy Co. Ltd.

地址：香港九龍旺角彌敦道610號荷李活商業中心18樓

電話：2960 0193

郵箱：cmli@live.hk

傳真：2960 0553

網址：http://www.hkre.com.hk/



RoHS